

RELEASE AGENTS

Desmolnet M

RELEASE AGENT FOR MOLDINGS

Product designed and formulated to prevent annoying adhesions in all types of molds intended for the creation of moldings on balconies, cornices, and decorative elements.

APPLICATIONS

Molds for moldings for balconies and cornices

Supports of plaster, expanded polystyrene, wood, polyester, and iron



FEATURES

- 01 Does not produce adhesions or leave residues on the support
- 02 Applicable to plaster, expanded polystyrene, wood, polyester, iron molds, etc.
- 03 Perfect finishes without the need for touch-ups

DIRECTIONS FOR USE

It will be applied with a brush or roller, giving a uniform layer over the entire mold, allowing to dry for 30 to 60 minutes before filling with concrete. In the case of plaster molds, it is advisable to apply at each demolding; in others, it will withstand several demoldings. At temperatures above 30 °C, it may cause a magnifying effect and melt the 'porex' mold; apply in the shade and, once dry, put into work.

TECHNICAL DATA

Aspect	Opaque liquid
Color	White
Density	0.7 ± 0.5 g/cc
Solubility in water	Insoluble
Active substance	100 %

PRODUCT DATA

COVERAGE

Between 3 and 4 m² per liter, depending on the support.

SAFETY

Flammable. Do not ingest. Safety data sheet available to professional users upon request.

R10 Flammable.

S2 Keep out of reach of children.