

RELEASE AGENTS

Desmolnet

WATER-DILUTABLE CONCRETE RELEASE AGENT

Release agent for concrete, water-dilutable, based on refined mineral oils, specially formulated to extend the lifespan of formwork sheets and boards. At the same time, it protects the sheets from oxidation.

APPLICATIONS

Wood, metal, or PVC formwork

Working rules



FEATURES

- 01 Designed for all types of molds: wood, metal, or PVC
- 02 Optimal release without affecting the finish
- 03 Protects sheets against oxidation
- 04 Also suitable for treating working rules

DIRECTIONS FOR USE

It is applied diluted in clear water in a proportion of between 5 and 15 liters of water per liter of Desmolnet. Once diluted, it is advisable to use it within 2 or 3 days, depending on the ambient temperature.

TECHNICAL DATA

Appearance	Transparent liquid
Color	Amber
Density	0.89 ± 0.01
Solubility in water	Soluble
Active substance	100 %

PRODUCT DATA

COVERAGE

Wood: between 5 and 20 parts of water.

Metal sheets: between 5 and 15 parts of water.

PVC molds: between 5 and 15 parts of water.

SAFETY

Do not ingest. Safety data sheet available to professional users upon request.

S2 Keep out of reach of children.

NOTES

In case of accidental ingestion, call the Toxicological Information Service: 915 62 04 20.