

WATERPROOFING

Elasnet 1

WATERPROOF AND ELASTIC COATING

A compound based on acrylic copolymers that is completely waterproof. Designed to solve waterproofing problems on roofs and terraces, as well as in numerous construction finishes. Especially suitable for terraces, planters, chimneys, gutters, and broken uralite.

APPLICATIONS

Terraces, roofs, and planters

Chimneys, gutters, and broken uralite

Waterproofing finishes



FEATURES

- 01 Superior elasticity of 550 %
- 02 Total waterproofing
- 03 Ideal for direct flooring on top
- 04 Suitable for horizontal and vertical surfaces

DIRECTIONS FOR USE

Apply a minimum of three crossed coats, preferably in different colors to avoid failures. Between coats, wait for the paint to be dry to the touch (approx. 3 h at 20 °C). Total curing in 15 days.

The substrate must be dry, clean, and as smooth as possible (use a trowel on mortar finishes).

QuimicaSur recommends reinforcing with synthetic mesh Mallasnet on surfaces larger than 25 m², according to standard UNE 53-410-87. On old or cracked terraces and roofs, reinforcement is essential. Do not paint in rain or threat of rain or with temperatures below 5 °C.

TECHNICAL DATA

Elasticity	550 %
Permeability	Good
Tensile strength	3.6 MPa
Bending at -5 °C	No cracks
Impact resistance	600
Accelerated aging	33 %
Thermal aging	29 % / 2.8 %

PRODUCT DATA

COMPOSITION

Acrylic copolymers, fillers, pigments, and additives.

COVERAGE

Three crossed coats at 0.5 kg/m² per coat.

SAFETY

Do not paint in rain or threat of rain or with temperatures below 5 °C. Do not ingest.

- S2** Keep out of reach of children.
- S24/25** Avoid contact with eyes and skin.
- S29** Do not dispose of waste in drains.
- S51** Use in well-ventilated areas.