

WATERPROOFING

Hidro-masa

WATER-REPELLENT ADDITIVE FOR CONCRETE AND MORTARS

Powerful water-repellent for mixing with mortars and concrete, achieving waterproofing of up to 99%. It also provides better plasticity and long life against carbonation and aluminosis. It does not alter transpiration (water vapor permeability).

APPLICATIONS

Water tanks and swimming pools

Walls and facing brick installation

Pavements, terraces, plastering and rendering



FEATURES

- 01 Waterproofing of up to 99%
- 02 Better plasticity of the mix
- 03 Protects against carbonation and aluminosis
- 04 Does not alter water vapor permeability
- 05 Prevents erosive action from freeze/thaw cycles
- 06 Complies with UNE-EN 480-5 for absorption

DIRECTIONS FOR USE

Mix the product at a rate of 250 cc per 50 kg bag of cement (175 cc per 35 kg bag) with part of the mixing water and add the mixture to the concrete mixer. Mix for at least 8 minutes; otherwise, the water-repellent power decreases. Increasing the recommended dose does not provide greater waterproofing.

TECHNICAL DATA

Appearance	Opaque liquid	
Color	White	
Odor	Characteristic	
Density	1.02 ± 0.01	
Solubility in water	Soluble	
Absorption test	CA expressed in g/mm ²	UNE-EN 480-5

PRODUCT DATA

COVERAGE

250 cc per 50 kg bag.
175 cc per 35 kg bag.
Mix for 8 minutes.

SAFETY

Biodegradable. Do not ingest. Industrial product for professional use.

S2 Keep out of reach of children.

NOTES

In case of accidental ingestion, call the Toxicological Information Service: 915 62 04 20.