

WATERPROOFING

# Hidrofa D

## SURFACE WATER REPELLENT SOLVENT-BASED

Surface water repellent for the waterproofing of exposed work, stone, block, mortar, etc. Does not alter the breathability or appearance of the substrate.

### APPLICATIONS

Facade treatment against rain

Exposed work, plastering, and water-favorable concrete



### FEATURES

- 01 High penetration
- 02 Resistant to the alkalinity of cement
- 03 Prevents the formation of green moss, efflorescence, and algae
- 04 Once dry, it can be painted
- 05 Protects against dirt

### DIRECTIONS FOR USE

The substrate must be clean and dry. Not usable for the waterproofing of terraces or roofs. Apply Hidrofa-D as it is presented, with a brush, roller, or low-pressure spray, in a single coat. A second coat may alter the appearance of the surface.

## TECHNICAL DATA

Appearance	Transparent liquid
Color	Colorless
Odor	Characteristic
Density	0.79 ± 0.01
Solubility in water	Insoluble
Active substance	4.6 %

## PRODUCT DATA

### COMPOSITION

Water repellents and solvents.

### COVERAGE

Exposed rustic work: 3 m<sup>2</sup>/L.  
Fine exposed work: 4 m<sup>2</sup>/L.  
Concrete block: 4 m<sup>2</sup>/L.  
Mortar: 5 m<sup>2</sup>/L.

## SAFETY

Flammable. Harmful if swallowed. Toxic to aquatic organisms.

- R10** Flammable.
- R65** Harmful: if swallowed, it may cause lung damage.
- R51/53** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- S2** Keep out of the reach of children.
- S23** Do not breathe vapors.
- S24/25** Avoid contact with eyes and skin.
- S62** In case of ingestion, do not induce vomiting: seek medical attention immediately and show the label or container.

## NOTES

In case of accidental ingestion, call the Toxicological Information Service: 915 62 04 20.