

WATERPROOFING

Impermu A

WATERPROOFING EMULSION FOR BURIED SURFACES

Colloidal bituminous emulsion with resins, paste-like consistency and water-soluble. Its application creates a continuous film of waterproofing bitumen.

APPLICATIONS

Buried walls, foundations and party walls

Roof under tiles

Moisture protection

FEATURES

- 01 Water and cement alkalinity resistant
- 02 High penetration power
- 03 Good workability and easy application

DIRECTIONS FOR USE

The substrate must be clean and free of dust, oils, tar and lime. Homogenize the product before application. Apply with brush, roller or spray gun.

First coat: dilute 3 parts of water to one part of Impermu-A. Allow to dry and apply a second workable coat.

In hot periods, moisten the substrate before applying. Apply and cure the product at temperatures between 10 °C and 35 °C.

TECHNICAL DATA

Curing	Before 24 h after application	UNE 104281-3-13
Direct flame test	—	UNE 104281-3-12
Water resistance	—	UNE 104281-3-13
Flexibility	—	UNE 104281-3-11

PRODUCT DATA

COVERAGE

2.5 to 3 m² per kg, depending on the condition of the substrate and ambient temperature.

SAFETY

Do not ingest.

- R36/38** Irritates the eyes and skin.
- S20** Do not eat or drink during use.
- S36/37/39** Wear protective gear, goggles and gloves.
- S61** Do not dispose of in the environment.
- S2** Keep out of the reach of children.