

WATERPROOFING

# Impermu

## ANIONIC WATERPROOFING EMULSION

Chemically modified emulsion with elastomer. Once cured, it forms a waterproof and highly elastic film.

### APPLICATIONS

Waterproofing of walls, foundations, and party walls

Roof under tiles

Vapor barrier for insulation chambers

Protection of conduits



### FEATURES

- 01 High elasticity even at low temperatures
- 02 Low thermal susceptibility
- 03 High adhesive power
- 04 Easy application

### DIRECTIONS FOR USE

The substrate must be clean of dust, grease, and tar. Homogenize the product before application. Prime with the substrate wet: Impermu diluted at 40% in water; let dry and apply a second coat diluted at 10%. Apply and cure the product at temperatures between 10 °C and 35 °C.

## TECHNICAL DATA

Brookfield viscosity	500 min.	NIE 008
Density	1.0–1.03 max.	UNE 104281-3-5
Softening point	45 min.	UNE EN 1427
Elastic recovery	35% min.	NLT 329

## PRODUCT DATA

### COVERAGE

2 to 2.5 m<sup>2</sup> per kg, depending on the condition of the substrate and ambient temperature.

## SAFETY

Irritant. Do not ingest. Industrial product for professional use.

- S2** Keep out of reach of children.
- S24/25** Avoid contact with eyes and skin.
- S29** Do not dispose of waste in drains.
- S51** Use in well-ventilated areas.