

WATERPROOFING

Sealpul 400

WALKABLE MEMBRANE RESISTANT TO UV RAYS

Single-component polyurethane, resistant to UV rays, highly elastic and walkable. It is used for the protection of waterproof membranes exposed to weather conditions.

APPLICATIONS

Protection of waterproof membranes exposed to weather conditions

FEATURES

- 01 Easy application
- 02 Resistant to standing water and ice
- 03 Maintains its properties from $-40\text{ }^{\circ}\text{C}$ to $+100\text{ }^{\circ}\text{C}$
- 04 Water vapor permeable
- 05 Walkable (only for people)
- 06 Stable color

DIRECTIONS FOR USE

It is applied with a roller or airless in one or two coats. Tool cleaning with Seal Solvent.

TECHNICAL DATA

Elongation at break	> 400 %
Hardness	65 ± 5
Water pressure resistance	No leakage (1 m column, 24 h)
Application temperature	5 °C to 35 °C

PRODUCT DATA

COVERAGE

120 to 200 g/m² depending on the condition of the substrate, humidity, and temperature.

SAFETY

Do not ingest. Do not drink or smoke during application. Safety data sheet available to professional users upon request.

R36/37 Use protective clothing and gloves.

S2 Keep out of reach of children.