

REPAIR MORTARS

Reparcemt Impreso Bicomponente

REPAIR MORTAR FOR PRINTED PAVEMENTS

Reparcemt Impreso is a fine surface repair mortar designed for leveling and aesthetic repair of concrete substrates, walls, and cornices, providing a fine finish similar to exposed concrete.

APPLICATIONS

Surface repair of concrete and prefabricated elements.

Leveling of substrates, walls, and cornices.

Achieving fine decorative finishes similar to exposed concrete.



FEATURES

- 01 Great adhesion to the substrate.
- 02 Water resistant.
- 03 Easy application and workability.
- 04 Protection against concrete carbonation.
- 05 No cracking.

DIRECTIONS FOR USE

Carefully clean and prepare the substrate before application. Remove dust, paint residues, loose particles, or contaminants that may affect adhesion.

Moisten the substrate before applying the product.

TECHNICAL DATA

Mortar density	1.7 g/cm ³
Mixing water	6 L / 25 kg bag
Curing time	3 min
Workability	30 min at 20 °C
Applicable thicknesses	1 to 5 mm
Application temperature	8 °C to 30 °C
Paintable with cement-based products	Approx. 4 h
Paintable with dispersions	Approx. 24 h

PRODUCT DATA

PACKAGING

Reparceint Impreso is supplied in sets of 15 kilograms.

STORAGE

Store in its original closed container, in a dry place protected from moisture and weather.

SAFETY

Reacts with water generating alkaline substances.

Do not ingest.

Industrial product for professional use.

S36/37/39 Wear protective clothing, gloves, and appropriate eye/face protection.

S2 Keep out of the reach of children.