

REPAIR MORTARS

# Reparnet Cosmetic

## SURFACE REPAIR MORTAR

Fine mortar designed for surface repairs: leveling of supports, walls, and cornices, with a fine finish resembling exposed concrete.

### APPLICATIONS

Repair of concrete and prefabricated surfaces

Leveling of supports, walls, and cornices

Fine finish resembling exposed concrete



### FEATURES

- 01 High adhesion
- 02 Water resistance
- 03 Easy to work with
- 04 Protects against concrete carbonation
- 05 No cracking

### DIRECTIONS FOR USE

Clean the support and carefully repair it. Moisten and apply while avoiding lumps. Let it rest for a few minutes and smooth after 30-60 minutes.

Use 6 liters of water for every 25 kg of Reparnet. In strong heat, assist curing with water.

## TECHNICAL DATA

Mortar density	1.7 g/cm <sup>3</sup>
Mixing water	6 L / 25 kg bag
Curing time	3 min.
Workability	30 min. at 20 °C
Applicable thicknesses	1 to 5 mm
Application temperature	8 °C to 30 °C
Paintable with cement-based products	Approx. 4 h
Paintable with dispersions	Approx. 24 h

## PRODUCT DATA

### COVERAGE

One 25 kg bag covers 1.5 m<sup>2</sup> at 10 mm thickness.

## SAFETY

Reacts with water generating alkaline substances. Do not ingest. Industrial product for professional use.

**S36/37/39** Wear suitable clothing and gloves; eye and face protection.

**S2** Keep out of the reach of children.