

RESINS

# Epoynet 2

## EPOXY MORTAR IN SELF-MIXING CARTRIDGES

Epoxy mortar in self-mixing cartridges thanks to its special nozzle, designed for high-strength anchors. It is referred to as a "chemical plug" when used in hollow substrates.

### APPLICATIONS

Joining any material, especially metal to concrete

Anchoring in hollow substrates (use sieves)



### FEATURES

- 01 High-strength anchors
- 02 Self-mixing cartridge: fast and precise application
- 03 Complies with ETAG 001-1 OPTION 7 certification
- 04 Total curing in 24-48 hours depending on temperature

### DIRECTIONS FOR USE

Unscrew the cap and screw on the special nozzle. Place in the applicator gun for 380 cc tubes. The substrate must be firm, clean, and free of dust. Discard any non-uniform mortar. Fill the drill hole and anchor the rod. The usage time depends on the ambient temperature and the substrate. Total curing in 24–48 hours.

---

**TECHNICAL DATA**

---

Appearance	Viscous paste	
Odor	Characteristic	
Density	1.6 g/ml	
Certification	ETAG 001-1 OPTION 7	ETAG 001-1

---

**SAFETY**

---

Irritant. Flammable. Irritates the eyes and skin. Do not dispose of in the environment.

**R10** Flammable.

**R36/38** Irritates the eyes and skin.

**S20** Do not eat or drink during use.

**S36/37/39** Wear protective gear, goggles, and gloves.

**S61** Do not dispose of in the environment.

**S2** Keep out of reach of children.

---

**NOTES**

---

*In case of accidental ingestion, call the Toxicological Information Service: 915 62 04 20.*