

RESINS

Floor Sealer

SOLVENT-BASED SEALING FOR FLOORS

Solvent-based acrylic sealer, suitable for the treatment of cement, concrete, terrazzo, natural stone, facing bricks or hard floors. Provides liquid and dust repellency, compacts cement and aggregate particles, increases mechanical resistance to abrasion and wear, and exhibits high chemical resistance to acids, alkalis, fats, and oils.

APPLICATIONS

Cement, concrete, terrazzo, and natural stone floors

Facing bricks and hard floors

FEATURES

- 01 Water and dust repellent effect
- 02 Improves surface compaction
- 03 Increases resistance to abrasion and wear
- 04 High chemical resistance to acids, alkalis, fats, and oils

DIRECTIONS FOR USE

Ensure that the surface is dry and clean. If the surface is not very porous, treat it with a 5–8% solution of Limpiacem to open pores. Once clean and dry, apply the first coat with a roller; the second can be applied 30 minutes to 1 hour later. We recommend applying in several thin and homogeneous layers so that the solvent evaporates before drying and no occlusions occur.

TECHNICAL DATA

Appearance	Viscous liquid
Color	Colorless
Flash point	Approx. 5 °C
Density (20 °C)	Approx. 0.9 g/cc

PRODUCT DATA**COMPOSITION**

Aromatic organic diluents and acrylic copolymer.

COVERAGE

2 to 3 m² per liter, in three layers.

SAFETY

Contains toluene. Easily flammable. Irritates the skin. Keep away from all flames or sources of sparks.

- R11** Easily flammable.
- R38** Irritates the skin.
- S7/9** Keep the container tightly closed and in a dry place.
- S16** Keep away from all flames or sources of sparks. No smoking.
- S36/37** Wear suitable protective clothing and gloves.
- S46** In case of ingestion, seek medical attention immediately and show the label or container.
- S2** Keep out of the reach of children.