

RESINS

# Promores 5

## BONDING BRIDGE WITH TACKING

Acrylic polymer resin in aqueous dispersion, with high adhesion and tack power. Acts as a bonding bridge or primer layer to facilitate the subsequent adhesion of mortar or plaster to different substrates.

### APPLICATIONS

Bonding old concrete and new concrete, mortars and plasters

Priming prior to the placement of tiles vertically or horizontally



### FEATURES

- 01 Permanent film, highly elastic and very sticky
- 02 Alkali resistant
- 03 Ensures the adhesion of mortars and plasters
- 04 Increases plasticity and reduces mixing water when adding to mortars

### DIRECTIONS FOR USE

The substrate must be clean, dry, and free of grease or dust. Apply with a brush or roller, avoiding puddles. Allow to dry before applying the mortar. Tools and splashes can be cleaned with water while still fresh.

Minimum drying time: 45 min (depending on substrate, temperature, layer thickness, and humidity).

---

**TECHNICAL DATA**

---

Color	White liquid
Solid content	52 %
Viscosity	3500 ± 500 mPa·s
Specific gravity	1.05 g/cm <sup>3</sup>
Tack time	One month
Adhesion	Approx. 0.6 MPa

---

**PRODUCT DATA**

---

**COVERAGE**

Between 6 and 8 m<sup>2</sup> per liter, depending on the condition of the substrate.

---

**SAFETY**

---

This is not a hazardous product in the sense of EU directives. Do not ingest.

**S2** Keep out of reach of children.